## अनुरक्षण एवं अभियांत्रिकी इकाई **MAINTENANCE & ENGINEERING UNIT** भाकृअनुप-भारतीय कृषि अनुसंधान संस्थान ICAR-INDIAN AGRICULTURAL RESEARCH INSTITUTE नई दिल्ली-१२ **NEW DELHI-12.**

No. 29-22/20-21/MEU

Date: 04.12.2020

## SHORT QUOTATION NOTICE

Item rate sealed Quotation are hereby invited on behalf of the Director, IARI from the Contractors Registered with CPWD, MES, Railways, MCD, PWD or other Central/State Govt./Semi Govt.agencies. The contractor must have valid IT-PAN, VAT, TIN and service tax registration number and having experience of two similar nature of works in last three years for the work mentioned below :

S. N	Name of work	Estimated cost / Item Rate	Earnest Money	
1.	Repair in lecture hall and room no. 203 in the division of Fruits & Horticultural Technology at IARI-ICAR, New Delhi-12.	Rs. 97,854.00	Rs. 2,000.00	

Last date for receipt of applications for sale of quotation

: .21.12.2020 Submission of quotation : up to 14:30 hours of 22.12.2020 Opening of quotation : 15:00 hours of 22.12.2020

Desirous and eligible agencies to download the schedule and details may visit IARI website www.iari.res.in or http://eprocure.gov.in and deposit the fee of Rs. 150/- (non-refundable) along with requisite EMD at the time of filing of Quotation. The rates on schedule and requisite eligibility documents should be filed in a separate envelopes submitted both together in a bigger envelope in case the Quotation is downloaded from the net, else the Quotation will be rejected. The schedule of work can also be purchased on payment of Rs. 150/- (non-refundable) from Tender Cell of M.E.Unit, Directorate during office hours on any working day by producing the eligibility documents and depositing the earnest money in the form of PO/DD favoring "Director, IARI, New Delhi-12." The Director IARI reserves the right to reject or accept any Quotation without assigning any reason. Quotations shall be submitted along with forwarding letter addressed to Director IARI otherwise quotation will not be considered.

Asstt. Admn. Officer (Works)

## Copy to:-

- 1. Comptroller Directorate for kind information please.
- 2. F. & A.O.(Audit-IV)
- 3. AAO (Contingency).
- 4. In-charge USI to display on website. (The Quotation Notice already sent to IARI web master)

	pair in lecture hall and room no. 203 in the division of Fruits & Horticultura	l technolo	gy at IA	29-22/ RI Pusa No.	20-21/ME
.No			by at in	in rusa, ive	v Deini-1.
1	Particular	Qty.	Unit	Rate	Amount
7	Dismantling old plaster or skirting raking out joints and cleaning the	ATTEN S			
	surface for plaster including disposal of rubbish to the dumping ground	Service Services			
2	within 50 metres lead.	62.00	sqn	39.00	24:
2	Dismantling aluminium/ Gypsum partitions, doors, windows, fixed glazing	Mar. 2265	1000	ATT THE SE	Tage of
	and false ceiling including disposal of unserviceable material and stacking		Scale L	To the last	
	of serviceable material with in 50 meters lead as directed by Engineer-in-			Total Table	S1-20-7 (G)
3	charge.	26.00	sqm	42.00	109
2	18 mm cement plaster in two coats under layer 12 mm thick cement	197 de 1	ET VENT	22 M 200	and in the Pa
	plaster 1:5 (1 cement : 5 coarse sand) finished with a top layer 6 mm thick cement plaster 1:6 (1 cement : 6 fine sand).			des rations	
4	Cutting holes up to 30x30 cm in walls including making good the same:	62.00	sqm	399.30	2475
	rolls up to 30x30 cm in walls including making good the same:		- tillas	Server But	3000 51
	With common burnt clay F.P.S. (non modular) bricks	10.00		Anna A	
5	Steel work in built up tubular (round, square or rectangular hollow tubes	10.00	each	327.25	327
	etc.) trusses etc., including cutting, hoisting, fixing in position and		3 2 3 4 5 1		
	applying a priming coat of approved steel primer, including welding and				
	bolted with special shaped washers etc. complete.				
	Hot finished welded type tubes	126.00	-		
	Refixing of existing false ceiling, as per the direction of engineer-in-	126.00	kg	143.45	1807
	engineer.	21.00			
7	Providing and fixing tiled false ceiling of specified materials of size 595x595 mm in true horizontal	21.00	sqm	768.31	1613
	icrei, suspended on inter locking metal grid of hot dinned galvanized stool sections ( t t t			Re-LIVE	
	120 grains/ squi, both side inclusive) consisting of main "T" rupper with suitable second to				
	get required length and of size 24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick (minimum)				
	since, 1200 min long spaced between main "T" at 600 mm center to center to feet				
	12200000 Hill and secondary cross "1" of length 600 mm and size 24v25 mm made at 0.20				
	thick (minimum) sheet to be interlocked at middle of the 1200x600 mm panel to form grids of 500x600 mm and wall angle of size 24x24x0.3 mm and laying false ceiling tiles of approved texture				
1.	the grid including, required cutting/making, opening for services like diffusors, will be a		E L		
1	miles, fixtures, smoke detectors etc. Main "T" runners to be suspended from				
1	notice clears of size 2/ x 3/ x 25 x1.6 mm fixed to ceiling with 12.5 mm dia and 50 and 50				
S	asteners, 4 mm GI adjustable rods with galvanised butterfly level clips of size 85 x 30 x 0.8 mm paced at 1200 mm center to center along main T, bottom exposed width of 24 mm of all T-				
13	certons shall be pre-painted with polyester paint, all complete for all heights as not as all form				
0	rawings and as directed by Engineer-in-charge.				
1	2.5 mm thick square edge PVC Laminated Gypsum Tile of size 595x595 mm, made of Gypsum				
12	distributed, manufactured from natural gynsiim as nor is 2005 nort land to				
1-	The related to the related to the tare side and 12misson material to the state of t				
	and side with an edges sealed Mith				
b	ne face side PVC film which goes around and wraps the edges and is bonded to the edges and the ack side metalized polyester film so as to make the tile a				
CC	empletely sealed unit.	5.00	sqm	1880.95	0405
P	roviding and laying in position cement concrete of specified grade	0.00	Sqiii	1000.93	9405
е	xcluding the cost of centering and shuttering - All work up to plinth level				
1:					
11	2.4 (1 cement : / coarse sand (zone-III) · / graded stars				
1	:2:4 (1 cement : 2 coarse sand (zone-III) : 4 graded stone				
a	ggregate 20 mm nominal size)	0.25	cum	6788.60	1697
P	ggregate 20 mm nominal size) roviding and applying white cement based putty of average thickness 1	0.25	cum	6788.60	1697
P	roviding and applying white cement based putty of average thickness 1 am, of approved brand and manufacturer, over the plastered wall	0.25	cum	6788.60	1697
P	ggregate 20 mm nominal size) roviding and applying white cement based putty of average thickness 1	0.25	cum	6788.60	1697
P m st	roviding and applying white cement based putty of average thickness 1 im, of approved brand and manufacturer, over the plastered wall urface to prepare the surface even and smooth complete.	36.00	cum		1697 4145
P m su	roviding and applying white cement based putty of average thickness 1 im, of approved brand and manufacturer, over the plastered wall urface to prepare the surface even and smooth complete.			6788.60	
P m su Di	roviding and applying white cement based putty of average thickness 1 am, of approved brand and manufacturer, over the plastered wall urface to prepare the surface even and smooth complete.  istempering with 1st quality acrylic distemper (ready mixed) aving VOC content less than 50 gms/litre, of approved manufacturer, of				
P m su Di ha re	roviding and applying white cement based putty of average thickness 1 am, of approved brand and manufacturer, over the plastered wall urface to prepare the surface even and smooth complete.  Isstempering with 1st quality acrylic distemper (ready mixed) awing VOC content less than 50 gms/litre, of approved manufacturer, of quired shade and colour complete, as per				
Di ha re	roviding and applying white cement based putty of average thickness 1 am, of approved brand and manufacturer, over the plastered wall urface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.				
Di ha re	roviding and applying white cement based putty of average thickness 1 am, of approved brand and manufacturer, over the plastered wall urface to prepare the surface even and smooth complete.  Istempering with 1st quality acrylic distemper (ready mixed) aving VOC content less than 50 gms/litre, of approved manufacturer, of quired shade and colour complete, as per anufacturer's specification.	36.00	sqm	115.15	4145
Di ha	roviding and applying white cement based putty of average thickness 1 am, of approved brand and manufacturer, over the plastered wall urface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.  In the surface to prepare the surface even and smooth complete.				

		130.00	sqm	54.30	7059
12	Old work (one or more coats)  Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by truck of capacity upto 5 cum capacity, including loading, transporting, unloading to approved municipal dumping ground or approved by Engineer-in-charge.		trip	2500.00	2500 97854
100	TOTAL			200	

Subject to be following terms & conditions:-

- 1. The work shall be executed as per CPWD specifications.
- 2. Income Tax, work Tax & work cess as per norms shall be recovered from the bill.
- 3. 1% water and electrical charges will be recovered from the bill if supplied by the Department.
- 4. The work shall start within 2 days from the date of award and complete within 20 days failing which a penalty @ 1% per day delay will be imposed on the bill amount maximum upto 10%.
- 5.All the materials, laboures, T&P etc. required will be arranged by the firms itself.
- 6. Other item to be required at site to complete the work will be executed as per the lowest quoted rates on DSR-2018.
- 7. The rates shall remain valid for 90 days from the date of opening of quotations/tenders.
- ctor. IARI has the right to reject any or all the quotation/tenders without assigning any reason.

centage rate to be quoted above or below in figure	
	The second secon
vords:	. 11
	( ) tu
I/C(W & CTO)	S.T.A(C)